

PHANTOM



1651102 • Gloss Jet black /
Smoke Lens



1651107 • Gloss Jet black /
Grey Polarized Len



28 g

- + RUBBER NOSE PADS AND TEMPLE TIPS
FOR SUPERIOR COMFORT AND A NON-SLIP FIT**
- + GREY POLARIZED LENS, TRUE COLOUR DEFINITION
WHILST FIGHTING HARSH GLARE**
- + 'ALS' ANTI-FOG/ANTI-SCRATCH COATING**

bollé
SAFETY

PHANTOM

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
PHANTOM	 Gloss Jet Black / Smoke Lens	1653601	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Gloss Jet Black / Grey Polarised Lens	1653602	I3	AS/NZS 1337.1.2010	Hard Coat

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 1. Range of luminous transmittance 43 -88% (twilight).
- 3. Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Assembly and production work
- Emergency response
- Driving
- Solar UV exposure
- Rigging
- High glare, outdoor work places

MAIN MARKETS

- Mining
- Manufacturing
- Transport
- Construction
- Local Government/
Councils
- Utilities

LENSES

- 2mm polycarbonate
- 8 base curve
- 'ALS' anti-fog/anti-scratch coating on both sides of the lens: Smoke only
- 100% UV400: Smoke, Polarized

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **BOLLÉ CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	PC + TPR
STRAP	No
FOAM	No
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

NEW ZEALAND:

Bollé New Zealand Limited
Unit 5, 114 Sawyers Arms Road
Papanui, Christchurch 8052
T: 03 3751400
E: bolle@bolle.co.nz